

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
21 February 2002 (21.02.2002)


PCT

(10) International Publication Number  
**WO 02/14092 A1**

- (51) International Patent Classification<sup>7</sup>: B60F 3/00, F16D 23/04, 3/20
- (21) International Application Number: PCT/GB01/03493
- (22) International Filing Date: 6 August 2001 (06.08.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0019783.0 12 August 2000 (12.08.2000) GB  
0019782.2 12 August 2000 (12.08.2000) GB
- (71) Applicant (for all designated States except US): GIBBS INTERNATIONAL TECHNOLOGIES LIMITED [I]; La Motte Chambers, St Helier, Jersey JE1 1BJ (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): ROYCROFT, Terence, James [NZ/NZ]; Awhitu, RD4 Waiuku (NZ).
- (74) Agents: CHURCH, Simon, John et al.; Lewis & Taylor, 144 New Walk, Leicester LE17JA (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: AMPHIBIOUS VEHICLE COMPRISING AN IMPROVED DECOUPLER



(57) Abstract: A decoupler for coupling/decoupling drive between a power train output and road wheels or marine drive means in an amphibious vehicle, is integrated with a constant velocity joint, saving space, weight, and cost for low production volumes, and simplifying mounting arrangements. Power train output shaft (14) enters casing (12) through aperture (16), and terminates in a flange (20) with splines (22). Baulk ring (50) and synchrocone (48) provide synchromesh action between drive ring (24) and driven CV joint cap (44). Rod (30) is attached to selector arm (28), located in slot (26), allowing coupling and decoupling by an external control, which may be assisted by a pneumatic or hydraulic cylinder (not shown). Fig. 2 shows the coupled state. The synchromesh parts may be sourced from truck gearboxes. CV joint (34) is mounted in bearings (36), and may be a Rzeppa type. Groove (59) allows fitment of a conventional dust gaiter (not shown):



WO 02/14092 A1



(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Declaration under Rule 4.17:**

— of inventorship (Rule 4.17(iv)) for US only

## AMPHIBIOUS VEHICLE COMPRISING AN IMPROVED DECOUPLER

The present invention relates to an amphibious vehicle having a decoupler for coupling/decoupling a drive shaft of the vehicle, and more particularly to an amphibious vehicle having a drive-shaft decoupler for engaging and disengaging a drive shaft which  
5 driveably connects an output from a power train of the vehicle with the wheels or marine propulsion system of the vehicle.

It has been found convenient to drive the marine propulsion systems of an amphibious vehicle through the transmission by which the wheels are also driven. With this arrangement it is necessary to disengage the drive to the wheels while the drive to the marine propulsion  
10 is engaged when the amphibious vehicle is in water mode. It is also desirable to be able to decouple and couple the drive to the wheels and marine propulsion system independently of one another as the vehicle makes the transition between land and marine modes of travel.

In the case of a transmission which incorporates a final-drive and differential unit as an integrated part of the whole transmission, it would only be possible to incorporate a  
15 decoupler into the transmission by designing a new internal arrangement. For amphibious vehicles, which are used in specialized applications and are produced in relatively low volumes, a dedicated transmission would be prohibitively expensive.

Therefore, on an amphibious vehicle in which the engine drives the road wheels and the  
20 marine propulsion system through an integrated transmission/differential, it has been found necessary to provide external drive shaft decouplers to disconnect the drive between the differential and the driven wheels, and between the transmission and the marine propulsion system. Typically a decoupler is provided in the driveline between the transmission and each driven wheel. However, it is possible to use a decoupler in the driveline between the  
25 transmission and only one of the driven wheels, since disconnecting drive to one of the driven wheels will effectively disengage drive to both wheels due to the effects of the

differential.

A problem with known external drive shaft decouplers is the amount of extra space they require. This is a particular problem in amphibious vehicles in which the wheels are designed to retract upwardly and inboard of the vehicle for use of the vehicle in water. In such vehicles  
5 the provision of wheel retraction systems and specialized suspension systems reduces the available space for external drive shaft decouplers.

A further problem which arises is the need to synchronise the speeds of the input and output means of the decoupler when drive is being coupled. This problem arises, for example, when the vehicle is preparing to leave the water with the wheels deployed. In these circumstances  
10 it is necessary for drive to be maintained to the marine propulsion system, in order to push the vehicle towards the shore, whilst drive to the road wheels is coupled. This enables the vehicle to propel itself out of the water using a combination of drive from the marine propulsion system and the road wheels. It is necessary, therefore, for the decoupler to have a clutch means to progressively engage the drive between the differential output of the  
15 transmission (which may be spinning at 1000 RPM), and a rotating assembly consisting of the drive shaft, brake disc, hub and wheel (which initially will be stationary in the water) representing the inertia to be overcome.

A similar problem arises when the vehicle enters the water, when it is desirable to couple drive to the marine propulsion system whilst drive to the road wheels is maintained. This  
20 enables a smooth transition from land to waterborne use of the vehicle but requires a stationary marine propulsion system to be coupled to a rotating power take-off shaft of the transmission.

Furthermore, where the decoupler is to be used in the driveline between the transmission and a drive shaft for a wheel of an amphibious vehicle, the decoupler must be capable of handling  
25 the high torque loads which are experienced by the drive shaft. For example very high torque loads are experienced in such drive shafts when drive to the wheels is engaged, wherein engine torque (say 250 Nm) is multiplied by a first gear ratio (say 4:1) times a final drive

ratio (say 3.5:1) :

$$250 \times 4 \times 3.5 = 3500 \text{ Nm}$$

When shock-loads from wheel/ground-contact torque reactions are factored in, it is common to allow for 10-12,000 Nm peak torque loads for the drive shafts of an average sized road  
5 vehicle.

It is an object of the invention to provide an amphibious vehicle having a decoupler which is capable of meeting the above requirements and which requires less space than known decouplers.

In accordance with the invention there is provided an amphibious vehicle comprising a  
10 decoupler for coupling/decoupling drive between an output from a the vehicle power train and a component to be driven, characterised in that the decoupler comprises a synchroniser adapted to synchronise the speed of an input means and an output means of the decoupler when drive is being coupled, and in that the decoupler forms part of an integrated unit also comprising a constant velocity joint.

15 By integrating a decoupler with synchroniser and a constant velocity joint into a single unit, the integrated unit can be positioned in the space usually taken up by a conventional constant velocity joint. Thus, the integrated unit requires less space than would be the case if a separate decoupler and constant velocity joint were to be used. Furthermore, there is a reduction in the number of components required and the mounting arrangements are  
20 simplified. This reduces the weight of the vehicle, the manufacturing and assembly costs of the vehicle and improves reliability.

In a particularly preferred embodiment the synchroniser is a synchromesh device comprising a baulk-ring and a cone, the baulk-ring and cone of the synchroniser providing a graduated drive engagement means.

This arrangement has the added advantage that a known synchromesh device from a conventional gearbox can be adopted for use in the decoupler. This enables the synchroniser device of the decoupler to be manufactured using commercially available components at much lower cost than would be the case if the components were to be purpose designed and  
5 manufactured.

Whilst known synchromesh devices, as found in a conventional manual gearbox, perform the tasks of clutching and coupling/decoupling in a combined operation as an integrated mechanism, such devices have not previously been employed for other than their designed purpose of manual gear selection inside the conventional gearbox. In this respect it should  
10 be noted that the inertia loads residual in gearbox internal shafting are very much lower than those of a drive shaft and wheel submerged in water. Also drive torque in a gearbox is not subject to final-drive multiplication and extreme wheel-to-ground shock-loading.

However, extensive analysis and tests have indicated that the clutching requirement of a drive shaft decoupler for an amphibious vehicle could be sustained by a synchromesh comprising  
15 a baulk-ring and synchro-cone, provided it is subjected to a greatly reduced number of application cycles than that normally experienced in the life of a gearbox.

Subsequent extensive testing based on the precise requirements of a drive shaft decoupler for an amphibious vehicle with regard to inertia loadings, road-load inputs, torsional vibration frequencies, and amphibious duty-cycles, have proved that a heavy goods vehicle gearbox  
20 synchromesh is capable of performing these unaccustomed tasks of high-inertia clutching and high-torque coupling, while fitting within the cost and space specifications when designed into a dedicated decoupler casing as shown herewith.

An embodiment of the present invention will now be described by way of example only with reference to the accompanying drawings in which:

25 Figure 1 is a section through a decoupler of an amphibious vehicle in accordance with the invention, the decoupler is shown in the position in which drive is disengaged or decoupled;

Figure 2 is view similar to that of Figure 1 but showing the decoupler in the position in which drive is engaged or coupled; and

Figure 3 is a schematic plan view in section of an amphibious vehicle in accordance with the invention, showing a drive train including an engine, gearbox and three decouplers of the type shown in Figures 1 and 2.

Referring firstly to Figure 1, a decoupler incorporating a constant velocity CV joint is indicated generally at 10. The decoupler 10 is of the form of an integrated unit, which is housed in a casing 12. A driving shaft 14, which may be from the output stage of a gearbox or from a differential (not shown), enters the casing 12 through a circular aperture 16 to the left hand side of the casing 12 (as viewed), and is free to rotate within the casing. An oil seal 18 seals between the driving shaft 14 and the aperture 16. The driving shaft 14 comprises an input of the decoupler 10.

The driving shaft 14 terminates inside the casing 12 in a flange 20, the periphery of which is splined 22. A drive ring 24, which is correspondingly internally splined, is in permanent driving engagement with the spline 22 and rotates with the driving shaft 14. A circumferential slot 26 is provided in the periphery of the drive ring 24, and a selector arm 28 locates in the slot 26. A rod 30, which is mounted for reciprocating movement, indicated by arrow A, in a bore 32 of the casing 12, mounts the selector arm 28 at one end. A linkage (not shown) is provided to enable an operator of an associated vehicle (80, Figure 3) to selectively slide the rod 30 and selector arm 28 to a required position. Alternatively the movement of the rod 30 can be remotely controlled by means of a pneumatic or hydraulic cylinder (not shown).

A CV joint indicated generally at 34 is rotatably mounted in ball bearings 36 in the right hand side of the casing 12 (as viewed). An oil seal 38 seals between the casing 12 and the CV joint 34, with the roller bearings 36 sealed in a protected position inside the casing 12. The oil seal 38 and the roller bearings 36 are positionally aligned and supported in the casing 12 by a pair of circlips 40.

The end of the CV joint 34 facing the flange 20 of the driving shaft 14 is stepped at 42. A stepped cap 44 is rigidly mounted on the stepped end 42. The periphery of the outer step of the cap 44 is splined at 46, and the periphery of the inner step is provided with a synchro-cone 48. The spline 46 has the same form as the spline 22.

- 5 A baulk ring 50 formed as a truncated cone extending into a flange, is located between the stepped cap 44 of the CV joint 34, and the flange 20 of the driving shaft 14. The periphery of the flange of the baulk ring 50 is splined at 52, and the spline 52 also has the same form as the splines 22 and 46. The flange 20, the baulk ring 50 and the outer step of the cap 44 are of the same diameter and are concentric.
- 10 The CV joint 34 is of the "RZEPPA" type, and comprises splines 54, a plurality of roller balls 56, and a driven shaft 58 which comprises an output of the decoupler. Typically there are three or four roller balls 56 mounted in equally spaced arrangement about the periphery of the end of the drive shaft 58. The CV joint 34 is capable of an articulation of up to 45° away from the axis of the driving shaft 14 and includes a conventional dust gaiter (not shown)
- 15 which extends between the drive shaft 58 and a groove 59 provided in the body of the CV joint 54.

Although in the preferred embodiment the CV joint is of the Rzeppa type, it should be understood that any suitable type of CV joint could be used. For example, the CV joint could be any of the following: Tracta, Weiss, Tripode, AC, VL, UF, UFC, GI, GE, GIC, ARR or

20 Triplan type.

The operation of the decoupler 10 will now be described with reference also to Figure 2. In Figure 1 the decoupler 10 is shown uncoupled and coupling is effected by movement of the rod 30 to the right as viewed. As the rod 30 is moved, for example, by a hydraulic cylinder, (not shown) the selector arm 28, which is engaged in the circumferential slot 26 of the drive ring 24, moves the drive ring 24 in the spline 22 towards the CV joint 34. The internal spline

25 of the drive ring 24 engages the spline 52 of the baulk ring 50, and pushes the baulk ring 50 onto the synchro-cone 48. The baulk ring 50 rotates at the speed of the driving shaft 14 and



the frictional contact between the conical part of the baulk ring 50 and the synchro-cone 48, synchronises the speed of the stepped cap 44 and the CV joint 34 with the speed of the driving shaft 14. The arrangement of the baulk ring 50 synchro-cone 48 and drive ring 24 is commonly known as a synchromesh device.

- 5 Further movement of the drive ring 24 by the selector arm 28 causes the drive ring 24 to slide to a position engaging both the spline 46 of the cap 44 and the spline 22 of the driving shaft flange 20, as shown in Figure 2. The full torque of the driving shaft 14 can then be passed through the drive ring 24 to the driven shaft 58 of the CV joint 34.

- Referring now to Figure 3, an amphibious vehicle, indicated generally at 80, has a transverse  
10 power train 60. The power train 60 comprises an engine 62, an in-line gear box 64, a differential unit 66 driven from the gearbox and a transfer gearbox 67 driven from the differential. Drive is provided from the differential to a pair of drive shafts 68 which drive the rear wheels 69 of the vehicle, and from the transfer gearbox 67 to a third shaft 70 which drives a marine propulsion system in the form of a water jet 71. A decoupler 10, of the kind  
15 described above in relation to Figures 1 and 2, is provided between each of the rear wheel drive shafts 68 and the differential 66 and between the drive shaft 70 and the transfer gearbox 67. The decouplers 10 allow drive to be selectively and independently connected between the differential 66 and each of the rear wheel drive shafts 68 and between the transfer gearbox and the water jet drive shaft 70. In the arrangement shown, the drive shafts 68, 70 comprise  
20 the same part as the drive shaft referenced 58 in Figures 1 and 2.

- In the embodiment shown in Figure 3, a decoupler 10 is provided for each of the rear wheel drive shafts 68. However, in an alternative embodiment, a decoupler 10 may be provided for only one of the rear wheel drive shafts 68, the other drive shaft 68 being provided with a conventional CV joint or the like. Those skilled in the art will readily understand that  
25 decoupling drive to one of the rear wheels will effectively disengage drive to both of the rear wheels, due to the effects of the differential 66.

Similarly, it may not be considered essential to provide a decoupler in the marine propulsion

system drive, as it is feasible to allow the marine propulsion unit to freewheel when the amphibious vehicle is driven in road mode. This entails a small loss of power, which is undesirable; but allows simplification of the marine drive train.

Some amphibious vehicle power trains do not require any road wheel decouplers. These  
5 include power trains where the marine power takeoff is upstream of the road wheel transmission. For example, a sandwich power takeoff may be used between the engine and transmission, as shown in Figure 1 of our co-pending application no. GB0020887.6. In this case, road wheel decouplers are not required, because drive to the road wheels can be decoupled simply by placing the gearbox in neutral gear.

10 Road wheel decouplers are also not required where the marine power takeoff is from the timing end of the crankshaft, for example according to Figure 2 of our co-pending application no. GB0021007.0.

It will be understood from the above that although Figure 3 shows an amphibious vehicle with a transverse engined power train, the decoupler 10 is equally suitable for use with a  
15 longitudinally engined power train or indeed any power train arrangement suitable for use in an amphibious vehicle.

The decoupler 10 is especially suitable for use in an amphibious vehicle because of the limited space around the engine and drive shafts, and the need to keep the weight of the vehicle to a minimum.

20 It is not intended that the decoupler 10 be used to couple drive between the transmission and the wheels when the vehicle is on land when the torques to be coupled would be high. Rather, it is intended that the decoupler 10 will be used to couple drive to the wheels when the vehicle is afloat in water and the wheels (not shown) are able to spin almost unimpeded. By the time that the wheels reach land, the driving ring 24 of the decoupler 10 is fully engaged  
25 with the spline 46 of the CV joint. Furthermore, coupling of the drive shaft 70 and of the wheel drive shafts 68 will occur when the gearbox is in low gear, with the engine running at

low speed. This reduces the inertia to be overcome in synchronising speeds of the drive shafts 68, 70 with the driving shaft 14.

## Claims

1. An amphibious vehicle comprising a decoupler for coupling/decoupling drive between an output from the vehicle power train and a component to be driven, characterised in that the decoupler comprises a synchroniser to synchronise the speed of an input means and an output means of the decoupler when drive is being coupled,  
5 and in that the decoupler forms part of an integrated unit also comprising a constant velocity joint.
2. An amphibious vehicle as claimed in claim 1, in which the synchroniser is a synchromesh device comprising a baulk-ring and a cone, the baulk-ring and cone of  
10 the synchromesh device providing a graduated drive engagement means.
3. An amphibious vehicle as claimed in claim 2 in which a first set of splines is formed on the input means and a second set of splines is formed on the output means, the decoupler further comprising a drive ring having an inner surface on which is formed a third set of splines which are in permanent driving engagement with the splines on  
15 the input means, the drive ring being moveable between a first position in which the splines on the drive ring are in engagement with the splines on the input means but not with the splines on the output means, and a second position in which the splines on the drive ring are in engagement with the splines on the input means and the splines on the output means.  
20
4. An amphibious vehicle as claimed in claim 3, in which the cone is provided on the output means and the baulk ring is arranged between the cone and the input means, a fourth set of splines being provided on the baulk ring, the arrangement being such that as the drive ring is moved from the first position to the second position, the  
25 splines on the drive ring engage the splines on the baulk ring so that the baulk ring is rotated with the input means and is pushed into frictional contact with the cone.
5. An amphibious vehicle as claimed in any previous claim in which the constant

velocity joint comprises the output means.

6. An amphibious vehicle as claimed in any previous claim in which the constant velocity joint is a "RZEPPA" type joint.
7. An amphibious vehicle comprising a decoupler for coupling/decoupling drive  
5 between an output from a transmission of the vehicle and a component to be driven substantially as hereinbefore described with reference to and as shown in Figures 1 and 2 of the accompanying drawings.

1/3




Fig. 1

2/3




Fig.2

3/3




Fig.3



## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/GB 01/03493

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B60F3/00 F16D23/04 F16D3/20

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60F F16D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 15 30 577 A (DAIMLER-BENZ AG) 18 December 1969 (1969-12-18) page 8, last paragraph -page 9, paragraph 2; figure 1 page 12, paragraph 3 -page 13, paragraph 1; figure 3	1
A	WO 95 23074 A (ROYCROFT MARIE ANNE ;ROYCROFT TERENCE JAMES (NZ)) 31 August 1995 (1995-08-31) page 5, line 5 - line 8 figures 1A-C	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

9 November 2001

Date of mailing of the international search report

15/11/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Cauderlier, F

## INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 01/03493

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 1530577	A	18-12-1969	DE 1530577 A1	18-12-1969
WO 9523074	A	31-08-1995	NZ 250979 A	26-03-1996
			AU 683330 B2	06-11-1997
			AU 1162995 A	07-09-1995
			EP 0742761 A1	20-11-1996
			WO 9523074 A1	31-08-1995
			US RE36901 E	03-10-2000
			US 5531179 A	02-07-1996